

SAFETY DATA SHEET

Noxudol Body Spray

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name

Noxudol Body Spray

Product no.

32011

Unique formula identifier (UFI)

DCDE-D7RR-7D4E-JJXW

1.2. Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture

Corrosion inhibitor

Use descriptors (UK REACH)

Sectors of use	Description
LCS "IS"	Industrial uses: Uses of substances as such or in preparations at industrial sites
LCS "C"	Consumer uses: Private households (= general public = consumers)
Product category	Description
PC 14	Metal surface treatment products, including galvanic and electroplating products

Uses advised against

None known.

1.3. Details of the supplier of the safety data sheet

▼ Company and address

Auson AB

Verkstadsgatan 3
S-434 42 KUNGSBACKA
Sweden
+46 (0)300 56 20 00

Contact person

Nina Nyth

E-mail

nina.nyth@auson.se

Revision

06/04/2025

SDS Version

6.0

Date of previous version

30/11/2024 (5.0)

1.4. Emergency telephone number

Healthcare professionals: Dial 0344 892 0111 to reach The National Poisons Information Service (NPIS) (24 hour service)

General public:

England - Dial 111 to reach NHS 111 (24 hour service)

Scotland - Dial 112 to reach NHS 24 (24 hour service)

Wales - Dial 111 or 0845 4647 to reach NHS Direct (24 hour service)

See section 4 "First aid measures".

SECTION 2: Hazards identification

Classified according to Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

2.1. Classification of the substance or mixture

Aerosol 1; H222, H229, Extremely flammable aerosol. Pressurised container: May burst if heated.

Skin Irrit. 2; H315, Causes skin irritation.

Eye Irrit. 2; H319, Causes serious eye irritation.

STOT SE 3; H336, May cause drowsiness or dizziness.
Aquatic Chronic 2; H411, Toxic to aquatic life with long lasting effects.

2.2. Label elements

Hazard pictogram(s)



Signal word

Danger

Hazard statement(s)

Extremely flammable aerosol. Pressurised container: May burst if heated. (H222, H229)
Causes skin irritation. (H315)
Causes serious eye irritation. (H319)
May cause drowsiness or dizziness. (H336)
Toxic to aquatic life with long lasting effects. (H411)

Precautionary statement(s)

General

Keep out of reach of children. (P102)

Prevention

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. (P210)
Do not spray on an open flame or other ignition source. (P211)
Do not pierce or burn, even after use. (P251)
Avoid breathing spray. (P261)
Use only outdoors or in a well-ventilated area. (P271)
Avoid release to the environment. (P273)
Wear eye protection/protective gloves/protective clothing. (P280)

Response

IF ON SKIN: Wash with plenty of water and soap. (P302+P352)
Collect spillage. (P391)

Storage

Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122°F. (P410+P412)

Disposal

Dispose of contents/container in accordance with local regulation (P501)

▼ Hazardous substances

Propane
Methyl ethyl ketone
Acetic acid ethyl ester
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (Heptane)

Additional labelling

UFI: DCDE-D7RR-7D4E-JJXW

VOC

VOC content: 830 g/L
MAXIMUM VOC CONTENT (Phase II, category B/e: 840 g/L)

2.3. Other hazards

Additional warnings

In the event of leaks, high concentrations of gases can quickly form. They can be toxic, asphyxiating, or explosive.
This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.
This product does not contain any substances considered to be endocrine disruptors in accordance with the criteria set out in Commission Delegated Regulation (EU) 2017/2100 or Commission Regulation (EU) 2023/707.

SECTION 3: Composition/information on ingredients

3.1. Substances

Not applicable. This product is a mixture.

3.2. ▼ Mixtures

Product/substance	Identifiers	% w/w	Classification	Note
Propane	CAS No.: 74-98-6 EC No.: 200-827-9 UK-REACH: Index No.: 601-003-00-5	20 - 30 %	Flam. Gas 1A, H220	

Metyletylketon	CAS No.: 78-93-3 EC No.: 201-159-0 UK-REACH: Index No.: 606-002-00-3	5 - 10 %	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
Acetic acid ethyl ester	CAS No.: 141-78-6 EC No.: 205-500-4 UK-REACH: Index No.: 607-022-00-5	5 - 10 %	EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336	[1]
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (Heptane)	CAS No.: 64742-49-0 EC No.: 927-510-4 UK-REACH: Index No.:	10-15%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	[19]
Butane	CAS No.: 106-97-8 EC No.: 203-448-7 UK-REACH: Index No.: 601-004-00-0	5-10%	Flam. Gas 1A, H220	
Cyclohexane	CAS No.: 110-82-7 EC No.: 203-806-2 UK-REACH: Index No.: 601-017-00-1	5-10%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Acute 1, H400 Aquatic Chronic 1, H410	[1], [3]
Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics	CAS No.: 64742-49-0 EC No.: 920-750-0 UK-REACH: Index No.:	5-10%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 STOT SE 3, H336 Aquatic Chronic 2, H411	[19]
Butylacetate	CAS No.: 123-86-4 EC No.: 204-658-1 UK-REACH: Index No.:	5-10%	EUH066 Flam. Liq. 3, H226 STOT SE 3, H336	[1]
Naphtha (petroleum), hydrotreated light	CAS No.: 64742-49-0 EC No.: 921-024-6 UK-REACH: Index No.:	3-5%	Flam. Liq. 2, H225 Asp. Tox. 1, H304 Skin Irrit. 2, H315 STOT SE 3, H336 Aquatic Chronic 2, H411	[19]
Hydrocarbons, C9, aromatics	CAS No.: 64742-95-6 EC No.: 918-668-5 UK-REACH: Index No.:	1-3%	Flam. Liq. 3, H226 Asp. Tox. 1, H304 STOT SE 3, H335 STOT SE 3, H336 Aquatic Chronic 2, H411	[19]
Carbon black	CAS No.: 1333-86-4 EC No.: 215-609-9 UK-REACH: Index No.:	1 -2 %		[19]

See full text of H-phrases in section 16. Occupational exposure limits are listed in section 8, if these are available.

Other information

[1] European occupational exposure limit.

[3] According to UK REACH, Annex XVII, the substance is subject to restrictions.

[19] UVCB = Unknown or variable composition, complex reaction products or of biological materials

SECTION 4: First aid measures

4.1. Description of first aid measures

General information

In the case of accident: Contact a doctor or casualty department – take the label or this safety data sheet.
Contact a doctor if in doubt about the injured person's condition or if the symptoms persist. Never give an unconscious person water or other drink.

Inhalation

Upon breathing difficulties or irritation of the respiratory tract: Bring the person into fresh air and stay with him/her.

Skin contact

IF ON SKIN: Wash with plenty of water and soap.

Remove contaminated clothing and shoes. Ensure to wash exposed skin thoroughly with water and soap. DO NOT use solvents or thinners.

If skin irritation occurs: Get medical advice/attention.

Eye contact

If in eyes: Flush eyes immediately with plenty of water or isotonic water (20-30 °C) for at least 5 minutes and continue until irritation stops. Remove contact lenses. Make sure to flush under upper and lower eyelids. If irritation continues, contact a doctor. Continue flushing during transport.

Ingestion

If the person is conscious, rinse the mouth with water and stay with the person. Never give the person anything to drink.

In case of malaise, seek medical advice immediately and bring the safety data sheet or label from the product. Do not induce vomiting, unless recommended by the doctor. Have the person lean forward with head down to avoid inhalation of or choking on vomited material.

Burns

Rinse with water until pain stops then continue to rinse for 30 minutes.

4.2. ▼ Most important symptoms and effects, both acute and delayed

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.

Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system.

Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

4.3. Indication of any immediate medical attention and special treatment needed

If eye irritation persists: Get medical advice/attention.

Information to medics

Bring this safety data sheet or the label from this product.

SECTION 5: Firefighting measures

5.1. Extinguishing media

Suitable extinguishing media: Alcohol-resistant foam, carbon dioxide, powder, water mist.

Unsuitable extinguishing media: Waterjets should not be used, since they can spread the fire.

5.2. Special hazards arising from the substance or mixture

Extremely flammable aerosol. Pressurised container. In a fire or if heated, a pressure increase will occur and the container may burst.

In use may form flammable/explosive vapour-air mixture.

Fire will result in dense smoke. Exposure to combustion products may harm your health. Closed containers, which are exposed to fire, should be cooled with water. Do not allow fire-extinguishing water to enter the sewage system and nearby surface waters.

5.3. ▼ Advice for firefighters

Wear self-contained breathing apparatus and protective clothing to prevent contact. Upon direct exposure contact The National Poisons Information Service (dial 111, 24 h service) in order to obtain further advice.

Hazchem Code: None

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Accidental releases always pose a serious risk of fire or explosion.

Storages not yet ignited must be cooled by water mist. Remove flammable materials if conditions allow it. Ensure

sufficient ventilation.
Avoid direct contact with spilled substances.
Ensure adequate ventilation, especially in confined areas.
Avoid inhalation of vapours from spilled material.

6.2. Environmental precautions

Avoid discharge to lakes, streams, sewers, etc. In the event of leakage to the surroundings, contact local environmental authorities.

6.3. Methods and material for containment and cleaning up

Limit spillage and collect using granular absorbent or similar materials, and dispose of it in accordance with the regulations on dangerous waste.
Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations.
Wherever possible cleaning should be performed with normal cleaning agents. Avoid use of solvents.

6.4. Reference to other sections

See section 13 "Disposal considerations" on handling of waste.
See section 8 "Exposure controls/personal protection" for protective measures.

SECTION 7: Handling and storage

7.1. ▼ Precautions for safe handling

Avoid static electricity.
Protect electrical equipment in accordance with current standards. To divert static electricity during transmission, containers must be grounded and connected by wire with the receiving containers. Do not use spark-forming tools.
Do not spray on an open flame or other ignition source.
Do not pierce or burn, even after use.
Avoid contact during pregnancy and while nursing.
Smoking, drinking and consumption of food is not allowed in the work area.
See section 8 "Exposure controls/personal protection" for information on personal protection.

7.2. Conditions for safe storage, including any incompatibilities

Must be stored in a cool and well-ventilated area, away from possible sources of ignition.
Pressurized gas packs (spray cans, aerosol cans) must be stored behind a wire mesh, which allows gases to escape and holds back packs flying around.

Recommended storage material

Always store in containers of the same material as the original container.

Storage conditions

Dry, cool and well ventilated. Shelf life: 36 months

Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

7.3. Specific end use(s)

This product should only be used for applications quoted in section 1.2.

SECTION 8: Exposure controls/personal protection

8.1. ▼ Control parameters

Metyletylketon

Long term exposure limit (8 hours) (ppm): 200
Long term exposure limit (8 hours) (mg/m³): 600
Short term exposure limit (15 minutes) (ppm): 300
Short term exposure limit (15 minutes) (mg/m³): 899

Annotations:

BMVG = Biological Monitoring Guidance Value exists

Sk = Can be absorbed through the skin and lead to systemic toxicity.

Acetic acid ethyl ester

Long term exposure limit (8 hours) (ppm): 200
Short term exposure limit (15 minutes) (ppm): 400

Natural Calcium Carbonate

Long term exposure limit (8 hours) (mg/m³): 10(inhalable)/4(respirable)

Butane

Long term exposure limit (8 hours) (ppm): 600
Long term exposure limit (8 hours) (mg/m³): 1450
Short term exposure limit (15 minutes) (ppm): 750

Short term exposure limit (15 minutes) (mg/m³): 1810

Annotations:

Carc1 = Capable of causing cancer and/or heritable genetic damage if it contains more than 0.1% of buta-1,3-diene.

Cyclohexane

Long term exposure limit (8 hours) (ppm): 100

Long term exposure limit (8 hours) (mg/m³): 350

Short term exposure limit (15 minutes) (ppm): 300

Short term exposure limit (15 minutes) (mg/m³): 1050

Butylacetate

Long term exposure limit (8 hours) (ppm): 150

Long term exposure limit (8 hours) (mg/m³): 724

Short term exposure limit (15 minutes) (ppm): 200

Short term exposure limit (15 minutes) (mg/m³): 966

Carbon black

Long term exposure limit (8 hours) (mg/m³): 3,5

Short term exposure limit (15 minutes) (mg/m³): 7

The Control of Substances Hazardous to Health Regulations 2002. SI 2002/2677 The Stationery Office 2002.
EH40/2005 Workplace exposure limits (Fourth Edition 2020).

▼ DNEL

Acetic acid ethyl ester

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	37 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	63 mg/kg bw/day
Long term – Local effects - General population	Inhalation	367 mg/m ³
Long term – Local effects - Workers	Inhalation	734 mg/m ³
Long term – Systemic effects - General population	Inhalation	367 mg/m ³
Long term – Systemic effects - Workers	Inhalation	734 mg/m ³
Short term – Local effects - General population	Inhalation	734 mg/m ³
Short term – Local effects - Workers	Inhalation	1468 mg/m ³
Short term – Systemic effects - General population	Inhalation	734 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1468 mg/m ³
Long term – Systemic effects - General population	Oral	4.5 mg/kg bw/day

Butylacetate

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	3.4 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	7 mg/kg bw/day
Short term – Systemic effects - General population	Dermal	6 mg/kg bw/day
Short term – Systemic effects - Workers	Dermal	11 mg/kg bw/day
Long term – Local effects - General population	Inhalation	35.7 mg/m ³
Long term – Local effects - Workers	Inhalation	300 mg/m ³
Long term – Systemic effects - General population	Inhalation	12 mg/m ³
Long term – Systemic effects - Workers	Inhalation	48 mg/m ³
Short term – Local effects - General population	Inhalation	300 mg/m ³
Short term – Local effects - Workers	Inhalation	600 mg/m ³
Short term – Systemic effects - General population	Inhalation	300 mg/m ³
Short term – Systemic effects - Workers	Inhalation	600 mg/m ³
Long term – Systemic effects - General population	Oral	2 mg/kg bw/day
Short term – Systemic effects - General population	Oral	2 mg/kg bw/day

Carbon black

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Inhalation	60 µg/m ³
Long term – Systemic effects - Workers	Inhalation	1 mg/m ³

Cyclohexane

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	1186 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	2016 mg/kg bw/day
Long term – Local effects - General population	Inhalation	206 mg/m ³
Long term – Local effects - Workers	Inhalation	700 mg/m ³
Long term – Systemic effects - General population	Inhalation	206 mg/m ³
Long term – Systemic effects - Workers	Inhalation	700 mg/m ³
Short term – Local effects - General population	Inhalation	412 mg/m ³
Short term – Local effects - Workers	Inhalation	1400 mg/m ³
Short term – Systemic effects - General population	Inhalation	412 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1400 mg/m ³
Long term – Systemic effects - General population	Oral	59.4 mg/kg bw/day

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	178.57 mg/m ³
Long term – Local effects - Workers	Inhalation	837.5 mg/m ³
Long term – Systemic effects - General population	Inhalation	410 µg/m ³
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m ³
Short term – Local effects - General population	Inhalation	640 mg/m ³
Short term – Local effects - Workers	Inhalation	1066.67 mg/m ³
Short term – Systemic effects - General population	Inhalation	1152 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m ³

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (Heptane)

Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	149 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	300 mg/kg bw/day
Long term – Local effects - General population	Inhalation	178.57 mg/m ³
Long term – Local effects - Workers	Inhalation	837.5 mg/m ³
Long term – Systemic effects - General population	Inhalation	447 mg/m ³
Long term – Systemic effects - Workers	Inhalation	2085 mg/m ³
Short term – Local effects - General population	Inhalation	640 mg/m ³
Short term – Local effects - Workers	Inhalation	1066.67 mg/m ³
Short term – Systemic effects - General population	Inhalation	1152 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m ³
Long term – Systemic effects - General population	Oral	149 mg/kg bw/day

Hydrocarbons, C9, aromatics

Duration:	Route of exposure:	DNEL:
Long term – Local effects - General population	Inhalation	178.57 mg/m ³
Long term – Local effects - Workers	Inhalation	837.5 mg/m ³
Long term – Systemic effects - General population	Inhalation	410 µg/m ³
Long term – Systemic effects - Workers	Inhalation	1.9 mg/m ³
Short term – Local effects - General population	Inhalation	640 mg/m ³
Short term – Local effects - Workers	Inhalation	1066.67 mg/m ³

Short term – Systemic effects - General population	Inhalation	1152 mg/m ³
Short term – Systemic effects - Workers	Inhalation	1286.4 mg/m ³
Metyletylketon		
Duration:	Route of exposure:	DNEL:
Long term – Systemic effects - General population	Dermal	412 mg/kg bw/day
Long term – Systemic effects - Workers	Dermal	1161 mg/kg bw/day
Long term – Systemic effects - General population	Inhalation	106 mg/m ³
Long term – Systemic effects - Workers	Inhalation	600 mg/m ³
Short term – Systemic effects - General population	Inhalation	450 mg/m ³
Short term – Systemic effects - Workers	Inhalation	900 mg/m ³
Long term – Systemic effects - General population	Oral	31 mg/kg bw/day

▼ PNEC

Acetic acid ethyl ester

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		240 µg/L
Freshwater sediment		1.15 mg/kg
Intermittent release (freshwater)		1.65 mg/L
Marine water		24 µg/L
Marine water sediment		115 µg/kg
Predators		200 mg/kg
Sewage treatment plant		650 mg/L
Soil		148 µg/kg

Butylacetate

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		180 µg/L
Freshwater sediment		981 µg/kg
Intermittent release (freshwater)		360 µg/L
Marine water		18 µg/L
Marine water sediment		98.1 µg/kg
Sewage treatment plant		35.6 mg/L
Soil		90.3 µg/kg

Carbon black

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		50 mg/L

Cyclohexane

Route of exposure:	Duration of Exposure:	PNEC:
Freshwater		44.7 µg/L
Freshwater sediment		3.6 mg/kg
Intermittent release (freshwater)		9 µg/L
Intermittent release (marine water)		900 ng/L
Marine water		4.47 µg/L
Marine water sediment		360 µg/kg
Sewage treatment plant		3.24 mg/L
Soil		694 µg/kg

Metyletylketon

Route of exposure:	Duration of Exposure:	PNEC:
---------------------------	------------------------------	--------------

Freshwater	55.8 mg/L
Freshwater sediment	284.74 mg/kg
Intermittent release (freshwater)	55.8 mg/L
Marine water	55.8 mg/L
Marine water sediment	284.7 mg/kg
Predators	1 g/kg
Sewage treatment plant	709 mg/L
Soil	22.5 mg/kg

8.2. Exposure controls

Compliance with the given occupational exposure limits values should be controlled on a regular basis.

General recommendations

Smoking, drinking and consumption of food is not allowed in the work area.

Exposure scenarios

There are no exposure scenarios implemented for this product.

Exposure limits

Professional users are subjected to the legally set maximum concentrations for occupational exposure. See occupational hygiene limit values above.

Appropriate technical measures

Apply standard precautions during use of the product. Avoid inhalation of gas or dust.

Hygiene measures

Take off contaminated clothing and wash it before reuse.

Measures to avoid environmental exposure

Provide adequate general and local exhaust ventilation.

Individual protection measures, such as personal protective equipment

Generally

Use only UKCA marked protective equipment.

Respiratory Equipment

Type	Class	Colour	Standards
Respiratory protection is not needed in the event of adequate ventilation.			

Skin protection

Recommended	Type/Category	Standards
Wear appropriate protection clothing, e.g. coveralls in polypropylene or working clothes in cotton or polyester.	-	-



▼ Hand protection

Material	Glove thickness (mm)	Breakthrough time (min.)	Standards
Nitrile	0,38	> 480	EN374-2, EN16523-1, EN388



Eye protection

Type	Standards
Safety glasses	EN166



SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state

Aerosol

Colour

Black

Odour / Odour threshold

Solvent

pH

Not applicable - pH is not defined for non-aqueous systems

Density (g/cm³)

0.95 (20 °C)

Kinematic viscosity

Not applicable - product is an aerosol

Particle characteristics

Not applicable - product is an aerosol

Phase changes

Melting point/Freezing point (°C)

Not applicable - product is an aerosol

Softening point/range (°C)

Does not apply to aerosols.

Boiling point (°C)

-0.5

▼ Vapour pressure

4900 hPa (25 °C)

Relative vapour density

2,1

Decomposition temperature (°C)

Not applicable - product is an article

Data on fire and explosion hazards

Flash point (°C)

-60

Flammability (°C)

The material is ignitable.

Auto-ignition temperature (°C)

Not applicable - product is an aerosol

▼ Lower and upper explosion limit (% v/v)

No data available

Solubility

Solubility in water

Insoluble

n-octanol/water coefficient (LogKow)

Not applicable - based on structure

▼ Solubility in fat (g/L)

No data available.

9.2. Other information

VOC (g/l)

830

Oxidizing properties

Non-oxidizing

Other physical and chemical parameters

No data available.

SECTION 10: Stability and reactivity

10.1. Reactivity

No data available.

10.2. Chemical stability

The product is stable under the conditions, noted in section 7 "Handling and storage".

10.3. Possibility of hazardous reactions

None known.

10.4. Conditions to avoid

Avoid static electricity.

Do not expose to any forms of heat (e.g. solar radiation). May lead to excess pressure.

10.5. Incompatible materials

Strong acids, strong bases, strong oxidizing agents, and strong reducing agents.

10.6. ▼ Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008 as retained and amended in UK law

▼ Acute toxicity

Product/substance	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (Heptane)
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	> 5,840 mg/kg

Product/substance	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (Heptane)
Species:	Rat
Route of exposure:	Dermal
Test:	LD50
Result:	> 2,920 mg/kg

Product/substance	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (Heptane)
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	> 23.3 mg/l

Product/substance	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	> 5,000 mg/kg

Product/substance	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	> 2,800 mg/kg

Product/substance	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	> 23.3 mg/l

Product/substance	Naphtha (petroleum), hydrotreated light
Species:	Rat
Route of exposure:	Oral
Test:	LD50
Result:	> 5,840 mg/kg

Product/substance	Naphtha (petroleum), hydrotreated light
Species:	Rabbit
Route of exposure:	Dermal
Test:	LD50
Result:	> 2,920 mg/kg

Product/substance	Naphtha (petroleum), hydrotreated light
Species:	Rat
Route of exposure:	Inhalation
Test:	LC50
Result:	> 25.2 mg/l

Product/substance	Hydrocarbons, C9, aromatics
Test method:	OECD 401
Species:	Rat
Route of exposure:	Oral
Test:	LD50

Result: 3492 mg/kg

Product/substance: Hydrocarbons, C9, aromatics
 Test method: OECD 402
 Species: Rabbit
 Route of exposure: Dermal
 Test: LD50
 Result: > 3160 mg/kg

Product/substance: Hydrocarbons, C9, aromatics
 Test method: OECD 403
 Species: Rat
 Route of exposure: Inhalation
 Test: LC50
 Result: > 6193 mg/m³

Skin corrosion/irritation

Causes skin irritation.

Serious eye damage/irritation

Causes serious eye irritation.

Respiratory sensitisation

Based on available data, the classification criteria are not met.

Skin sensitisation

Based on available data, the classification criteria are not met.

Germ cell mutagenicity

The chemical structure does not suggest a mutagenic effect.

Carcinogenicity

Does not present any cancer hazards.

Reproductive toxicity

The chemical structure does not suggest such an effect.

STOT-single exposure

May cause drowsiness or dizziness.

STOT-repeated exposure

Based on available data, the classification criteria are not met.

Aspiration hazard

Not classified.

11.2. Information on other hazards

▼ Long term effects

Irritation effects: This product contains substances, which may cause irritation upon exposure to skin, eyes or lungs. Exposure may result in an increased absorption potential of other hazardous substances at the area of exposure.
 Neurotoxic effects: This product contains organic solvents, which may cause adverse effects to the nervous system. Symptoms of neurotoxicity include: loss of appetite, headache, dizziness, ringing in ears, tingling sensations of skin, sensitivity to the cold, cramps, difficulty in concentrating, tiredness, etc. Repeated exposure to solvents can result in the breaking down of the skin's natural fat layer and may result in an increased absorption potential of other hazardous substances at the area of exposure.

▼ Endocrine disrupting properties

This mixture/product does not contain any substances known to have hormone-disrupting properties in relation to health.

Other information

Carbon black has been classified by IARC as a group 2B carcinogen.

SECTION 12: Ecological information

12.1. ▼ Toxicity

Product/substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (Heptane)
 Species: Fish, *Oncorhynchus mykiss*
 Duration: 96 hours
 Test: LL50
 Result: > 13.4 mg/l

Product/substance: Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (Heptane)
 Species: Algae, *Selenastrum capricornutum*
 Duration: 72 hours
 Test: EL50
 Result: 10 -30 mg/l

Product/substance	Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (Heptane)
Species:	Crustacean, <i>Daphnia magna</i>
Duration:	48 hours
Test:	EL50
Result:	3 mg/l

Product/substance	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
Species:	Fish, <i>Oncorhynchus mykiss</i>
Duration:	96 hours
Test:	LL50
Result:	> 13.4 mg/l

Product/substance	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
Species:	Algae, <i>Selenastrum capricornutum</i>
Duration:	72 hours
Test:	EL50
Result:	10 -30 mg/l

Product/substance	Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics
Species:	Crustacean, <i>Daphnia magna</i>
Duration:	48 hours
Test:	EL50
Result:	3 mg/l

Product/substance	Naphtha (petroleum), hydrotreated light
Species:	Fish, <i>Oncorhynchus mykiss</i>
Duration:	96 hours
Test:	LL50
Result:	11.4 mg/l

Product/substance	Naphtha (petroleum), hydrotreated light
Species:	Algae, PHAEOPHYTA
Duration:	48 hours
Test:	EC50
Result:	10 mg/l

Product/substance	Naphtha (petroleum), hydrotreated light
Species:	Crustacean, <i>Daphnia magna</i>
Duration:	48 hours
Test:	EL50
Result:	3 mg/l

Product/substance	Hydrocarbons, C9, aromatics
Species:	Fish, <i>Oncorhynchus mykiss</i>
Duration:	No data available.
Test:	LL50
Result:	9,2 mg/l

Product/substance	Hydrocarbons, C9, aromatics
Species:	Algae, <i>Desmodesmus subspicatus</i>
Duration:	No data available.
Test:	ErL50
Result:	2,9 mg/l

Product/substance	Hydrocarbons, C9, aromatics
Species:	Crustacean, <i>Daphnia magna</i>
Duration:	No data available.
Test:	EL50
Result:	3,2 mg/l

Toxic to aquatic life with long lasting effects.

12.2. Persistence and degradability

Based on available data, the classification criteria are not met.

12.3. Bioaccumulative potential

Based on available data, the classification criteria are not met.

12.4. Mobility in soil

No data available.

12.5. Results of PBT and vPvB assessment

This mixture/product does not contain any substances known to fulfil the criteria for PBT and vPvB classification.

12.6. Endocrine disrupting properties

This mixture/product does not contain any substances considered to have endocrine-disrupting properties in relation to the environment.

12.7. Other adverse effects

This product contains substances that are toxic to the environment. May result in adverse effects to aquatic organisms.

This product contains substances, which may cause adverse long-term effects to the aquatic environment.

SECTION 13: Disposal considerations**Waste treatment methods**

Product is covered by the regulations on hazardous waste. (*)

HP 3 - Flammable

HP 4 - Irritant (skin irritation and eye damage)

HP 14 - Ecotoxic

Dispose of contents/container to an approved waste disposal plant.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

EWC code

13 02 05* Mineral-based non-chlorinated engine, gear and lubricating oils

Specific labelling**Contaminated packing**

Packaging containing residues of the product must be disposed of similarly to the product.

SECTION 14: Transport information

	14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other information:
ADR	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F  	-	Yes	Limited quantities: 1 L Tunnel restriction code: (D) See below for additional information.
IMDG	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F  	-	Yes	Limited quantities: 1 L EmS: F-D S-U See below for additional information.
IATA	UN1950	AEROSOLS	Transport hazard class: 2 Label: 2.1 Classification code: 5F 	-	Yes	See below for additional information.

14.1 UN / ID	14.2 UN proper shipping name	14.3 Hazard class(es)	14.4 PG*	14.5 Env**	Other informatio n:
					

* Packing group

** Environmental hazards

Additional information

This product is within scope of the regulations of transport of dangerous goods.

ADR / See Table A, section 3.2.1 for any information on special provisions, requirements, or warnings in connection with transport. See section 5.4.3, for instructions in writing regarding mitigation of damages in relation to incidents or accidents during transport.

IMDG / See section 3.2.1, for any information on special provisions, requirements, or warnings in connection with transport.

IATA / See Table 4.2 for any information on special provisions, requirements, or warnings in connection with transport.

Hazchem Code: None

14.6. Special precautions for user

Not applicable.

14.7. Maritime transport in bulk according to IMO instruments

No data available.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

Restrictions for application

People under the age of 18 shall not be exposed to this product.

Pregnant women and women breastfeeding must not be exposed to this product. The risk, and possible technical precautions or design of the workplace needed to eliminate exposure, must be considered.

Demands for specific education

No specific requirements.

Control of Major Accident Hazards (COMAH) - Categories / dangerous substances

P3a - FLAMMABLE AEROSOLS, Qualifying quantity (lower-tier): 150 tonnes (net) / (upper-tier): 500 tonnes (net)

E2 - ENVIRONMENTAL HAZARDS, Qualifying quantity (lower-tier): 200 tonnes / (upper-tier): 500 tonnes

Regulation on drug precursors

Metyletylketon is included (Category 3)

UK-REACH, Annex XVII

Cyclohexane is subject to restrictions, UK-REACH annex XVII (entry 57).

Propane is subject to UK-REACH restrictions (entry 40).

Metyletylketon is subject to UK-REACH restrictions (entry 40).

Acetic acid ethyl ester is subject to UK-REACH restrictions (entry 40).

Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics (Heptane) is subject to UK-REACH restrictions (entry 40).

Butane is subject to UK-REACH restrictions (entry 40).

Cyclohexane is subject to UK-REACH restrictions (entry 40).

Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics is subject to UK-REACH restrictions (entry 40).

Butylacetate is subject to UK-REACH restrictions (entry 40).

Naphtha (petroleum), hydrotreated light is subject to UK-REACH restrictions (entry 40).

Hydrocarbons, C9, aromatics is subject to UK-REACH restrictions (entry 40).

Additional information

Not applicable.

Sources

The Health and Safety at Work etc. Act 1974 Regulations 2013.

The Aerosol Dispensers Regulations 2009 No. 2824, amended in 2014 (No. 1130) and in 2018 (No. 29).

Control of Major Accident Hazards (COMAH) Regulations 2015.

2012 No. 1715 ENVIRONMENTAL PROTECTION: The Volatile Organic Compounds in Paints, Varnishes and Vehicle Refinishing Products Regulations 2012.

Regulation (EU) No 1357/2014 of 18 December 2014 on waste as retained and amended in UK law.

The Controlled Drugs (Drug Precursors) Regulations 2008.

Regulation (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures (CLP) as retained and amended in UK law.

Regulation (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals

(REACH) as retained and amended in UK law.

15.2. Chemical safety assessment

No

SECTION 16: Other information

▼ Full text of H-phrases as mentioned in section 3

EUH066, Repeated exposure may cause skin dryness or cracking.

H220, Extremely flammable gas.

H225, Highly flammable liquid and vapour.

H226, Flammable liquid and vapour.

H304, May be fatal if swallowed and enters airways.

H315, Causes skin irritation.

H319, Causes serious eye irritation.

H335, May cause respiratory irritation.

H336, May cause drowsiness or dizziness.

H400, Very toxic to aquatic life.

H410, Very toxic to aquatic life with long lasting effects.

H411, Toxic to aquatic life with long lasting effects.

The full text of identified uses as mentioned in section 1

LCS "IS" = Industrial uses: Uses of substances as such or in preparations at industrial sites

LCS "C" = Consumer uses: Private households (= general public = consumers)

PC 14 = Metal surface treatment products, including galvanic and electroplating products

Abbreviations and acronyms

ADN = European Provisions concerning the International Carriage of Dangerous Goods by Inland Waterway

ADR = The European Agreement concerning the International Carriage of Dangerous Goods by Road

ATE = Acute Toxicity Estimate

BCF = Bioconcentration Factor

CAS = Chemical Abstracts Service

CE = Conformité Européenne (European conformity)

CLP = Classification, Labelling and Packaging Regulation [Regulation (EC) No. 1272/2008]

CSA = Chemical Safety Assessment

CSR = Chemical Safety Report

DMEL = Derived Minimal Effect Level

DNEL = Derived No Effect Level

EINECS = European Inventory of Existing Commercial chemical Substances

ES = Exposure Scenario

EUH statement = CLP-specific Hazard statement

EuPCS = European Product Categorisation System

EWC = European Waste Catalogue

GHS = Globally Harmonized System of Classification and Labelling of Chemicals

GWP = Global warming potential

IARC = International Agency for Research on Cancer (IARC)

IATA = International Air Transport Association

IBC = Intermediate Bulk Container

IMDG = International Maritime Dangerous Goods

LogPow = logarithm of the octanol/water partition coefficient

MARPOL = International Convention for the Prevention of Pollution From Ships, 1973 as modified by the Protocol of 1978. ("Marpol" = marine pollution)

OECD = Organisation for Economic Co-operation and Development

PBT = Persistent, Bioaccumulative and Toxic

PNEC = Predicted No Effect Concentration

RID = The Regulations concerning the International Carriage of Dangerous Goods by Rail

RRN = REACH Registration Number

SCL = A specific concentration limit

SVHC = Substances of Very High Concern

STOT-RE = Specific Target Organ Toxicity - Repeated Exposure

STOT-SE = Specific Target Organ Toxicity - Single Exposure

TWA = Time weighted average

UN = United Nations

UVBC = Unknown or variable composition, complex reaction products or of biological materials

VOC = Volatile Organic Compound

vPvB = Very Persistent and Very Bioaccumulative

Additional information

The classification of the substance/mixture in regard of health hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the substance/mixture in regard of environmental hazards are in accordance with the calculation methods given by Regulation (EC) No. 1272/2008 (CLP) as retained and amended in UK law.

The classification of the mixture in regard to physical hazards has been based on experimental data.

[The safety data sheet is validated by](#)

Nina Nyth

Other

A change (in proportion to the last essential change (first cipher in SDS version, see section 1)) is marked with a triangle.

The information in this safety data sheet applies only to this specific product (mentioned in section 1) and is not necessarily correct for use with other chemicals/products.

It is recommended to hand over this safety data sheet to the actual user of the product. Information in this safety data sheet cannot be used as a product specification.

Country-language: GB-en